



### Measurements

**Platform length** ..... 1080 mm  
**Platform width** ..... 805 mm  
**Door height** ..... 2040 mm  
**Door width** ..... 800 mm

**Shaft depth** ..... 1340 mm  
**Shaft width** ..... 880 mm  
**Shaft height\*** ..... 5350 mm  
**Travel height\*\*** ..... 3000-9000 mm

**Top Height** ..... 2300 mm  
**Aperture depth** ..... 1370 mm  
**Aperture width** ..... 910 mm

\* Depending on travel height and top height. \*\* Differs per location.

**Lift Type:** Platform lift type Pluto

**Lifting capacity:** 2 persons/1 person in a wheelchair/225 kg

**Lifting height:** max. 12000 mm

**Top height:** 2300 mm

**Number of stops:** max. 4 stops

**Number of doors:** max. 1 doors per floor

**Operator controls:** "Hold to run" buttons

**Drive system:** A patented screw/ nut system

**Standard platform size:** 805 mm wide x 1080 mm deep

**Required floor area:** 880 mm wide x 1340 mm deep (for through floor applications 910 mm wide x 1370 mm deep)

**Electrical connection:** 1 phase 230V 50Hz/5.2A/16A slow

**Speed:** 0.15 m/s

**Control supply:** 24 V

**Motor:** 1.5 kW

**Technical compliance:**

European machine directive 98/37/EC

**Pit depth – if required:** 50 mm (with ramp no pit is necessary)

**Standard colour:** White (RAL9003)

### Features included on the standard lift:

- External door closer
- Large glass panel doors
- Interlocked entrance doors
- Battery operated emergency lowering
- School locking
- Ceiling
- Soft start
- Light fitting on back wall
- 25 mm thick panels
- Automatic lubrication system
- Call and send functionality
- Integrated service diagnostic system
- Automatic light shut down